

Product Catalog



BALL BEARINGS

600 Series	Type
608	2RS / ZZ /Open
6000 Series	Type
6000	2RS / ZZ
6001	2RS / ZZ
6002	2RS / ZZ
6003	2RS / ZZ
6004	2RS / ZZ
6005	2RS / ZZ
6006	2RS / ZZ
6007	2RS / ZZ
6008	2RS
6009	2RS
6010	2RS
6011	2RS
6012	2RS

6200 Series	Type
6200	2RS / ZZ
6201	2RS / ZZ
6202	2RS / ZZ
6203	2RS / ZZ
6204	2RS / ZZ
6205	2RS / ZZ
6206	2RS / ZZ
6207	2RS / ZZ
6208	2RS
6209	2RS
6210	2RS
6211	2RS
6212	2RS
Others	Type
99502H	2RS
99502HNR	2RS
RM2 V Groove	2RS
6003 Flanged	2RS
6202 Flanged	2RS

6300 Series	Type
6301	2RS
6302	2RS
6303	2RS
6304	2RS
6305	2RS
6306	2RS
6307	2RS
R Series	Type
R4	2RS / ZZ
R6	2RS / ZZ
R8	2RS / ZZ
R10	2RS / ZZ
R12	2RS / ZZ
R14	2RS
R16	2RS

OTHER BEARINGS

GARAGE DOOR ROLLERS
4" Stem with Protective Cap
4" Stem without Protective Cap
7" Stem without Protective Cap

TRAILER KITS
L44643/L44610 - 12192TB SEAL - OD 1.980"
L44649/L44610 - 12192TB SEAL - OD 1.980"

INSERT BEARINGS

SER SERIES	Bore Size
SER201-8	1/2"
SER202-10	5/8"
SER204-12	3/4"
SER205-16	1"

SER SERIES	Bore Size
SER206-20	1-1/4"
SER207-23	1-7/16"
SER209-28	1-3/4"
SER210-32	2"

SER SERIES	Bore Size
SER211-32	2"
SER212-38	2-3/8"
SER215-48	3"

MOUNTED BEARINGS

UCP200	Bore Size
UCP201-8	1/2"
UCP202-10	5/8"
UCP204-12	3/4"
UCP205-16	1"
UCP206-20	1-1/4"
UCP208-24	1-1/2"
UCP209-28	1-3/4"
UCP210-32	2"
UCP211-32	2"
UCP212-38	2-3/8"
UCP213-40	2-1/2"
UCP215-48	3"

UCF200	Bore Size
UCF201-8	1/2"
UCF202-10	5/8"
UCF204-12	3/4"
UCF205-16	1"
UCF206-20	1-1/4"
UCF207-20	1-1/4"
UCF208-24	1-1/2"
UCF209-28	1-3/4"
UCF210-32	2"
UCF211-32	2"
UCF212-39	2-7/16"
UCF213-40	2-1/2"
UCF215-47	2-15/16"

UCFL200	Bore Size
UCFL201-8	1/2"
UCFL202-10	5/8"
UCFL204-12	3/4"
UCFL205-16	1"
UCFL206-20	1-1/4"
UCFL208-24	1-1/2"

PRECISION BALLS

CHROME STEEL	
Diameter	Precision
3mm	G25
5mm	G25
6mm	G25
3/32"	G25
1/8"	G25
5/32"	G25
3/16"	G25
7/32"	G25
1/4"	G25
5/16"	G25
3/8"	G25
7/16"	G25
1/2"	G25
5/8"	G25
3/4"	G25
1"	G25
1-1/4"	G25
1-1/2"	G25
2"	G25
2-1/2"	G25
3"	G100
3-1/2"	G100

CARBON STEEL	
Diameter	Precision
1/8"	G500
3/16"	G500
1/4"	G500
3/8"	G500
5/16"	G500
1/2"	G500
3/4"	G100/G500
1"	G500
1-1/16"	G100

SOFT CARBON	
Diameter	Precision
1/4"	G1000
5/16"	G500
3/8"	G500
1/2"	G500

STAINLESS STEEL (AISI440c)	
Diameter	Precision
1/8"	G25
5/32"	G25
3/16"	G25
1/4"	G25
3/8"	G25
1/2"	G25
1"	G25

STAINLESS STEEL (AISI420)	
Diameter	Precision
1/8"	G40
3/16"	G40
1/4"	G40
5/16"	G40
3/8"	G40
1/2"	G40
3/4"	G40
1"	G40

GRINDING MEDIA	
Available in:	Chrome Steel (AISI52100) and Stainless Steel (AISI316)
Precision:	G500
Diameters available:	3mm, 5mm, 6mm, 10mm and 15mm.

ROLLER CHAINS

SINGLE STRANDED ROLLER CHAIN

ANSI	LENGTHS AVAILABLE					
	3ft	4ft	5ft	10ft	50ft	100ft
#25				X		X
#35	X	X	X	X	X	X
#40	X		X	X	X	X
#41	X			X	X	X
#50				X	X	
#60				X	X	
#80				X	X	
#100				X		
#120				X		
#140				X		
#160				X		
#180				X		
#200				X		

DUPLEX ROLLER CHAIN

ANSI	LENGTHS AVAILABLE					
	10ft					
#35-2				X		
#40-2				X		
#50-2				X		
#60-2				X		
#80-2				X		
#120-2				X		
#140-2				X		

TRIPLEX ROLLER CHAIN

ANSI	LENGTHS AVAILABLE					
	10ft					
#35-3				X		
#40-3				X		
#50-3				X		
#60-3				X		
#80-3				X		

STAINLESS STEEL ROLLER CHAINS

ANSI	LENGTHS AVAILABLE		
	10ft	50ft	100ft
#35SS	X		
#40SS	X	X	X
#41SS	X		X
#50SS	X	X	
#60SS	X	X	

NICKEL PLATED ROLLER CHAINS

ANSI	LENGTHS AVAILABLE		
	10ft		
#35NP		X	
#40NP		X	
#41NP		X	

HOLLOW PIN ROLLER CHAIN

ANSI	LENGTHS AVAILABLE		
	10ft		
#40HP		X	
#50HP		X	
#60HP		X	
#80HP		X	

FORKLIFT CHAINS

ANSI	LENGTHS AVAILABLE	
	10ft	50ft
#BL634	X	X
#BL546	X	

MOTORCYCLE ROLLER CHAINS

ANSI	LENGTHS AVAILABLE	
#420		102 links
#420		132 links
#420		240 links
#415H		110 links

HEAVY-DUTY ROLLER CHAINS		
ANSI	LENGTHS AVAILABLE	
	10ft	50ft
#25	X	
#40H	X	
#50H	X	
#60H	X	X
#80H	X	X
#100H	X	
#120H	X	
#140H	X	
#160H	X	
#180H	X	
#200H	X	
#C2060H	X	
#C2080H	X	

AGRICULTURAL, CONVEYOR, AND PINTLE CHAINS		
ANSI	LENGTHS AVAILABLE	
	10ft	100ft
#662	X	
#667H	X	
#667X	X	
#667HX	X	
#88K	X	
#88C	X	
#81X	X	
#CA620	X	
#C2060	X	
#C2080	X	
#CA550	X	
#A2050	X	X
#A2060	X	

CONNECTING LINKS
#25, #35, #35SS, #40, #40SS, #41, #41SS, #50, #50SS, #60, #60SS, #60H, #80 and #80H.
OFFSET LINKS
#35, #40, #41, #50, #60, #80, #80H and #420.

We offer specialized **Roller Chain Tools** designed to either Detach or Connect links, allowing you to easily shorten or lengthen your roller chains as needed. Our roller chain tools are crafted with precision and durability in mind, ensuring that they can handle the rigors of industrial use.

Compatible models for these tools include:
 #25, #35, #40, #41, #50, #60, #80, #100, #120, #140, #160, #180, #420, #425, #428, #415, #415H, #428H, #520, #525 & #530.

MIG WIRES

ER70S-6 - Mild Steel	
Wire Diameter	Spool Size
0.023"	2/10/33 lbs
0.030"	2/10/33 lbs
0.035"	2/10/33/44/550 lbs
0.045"	2/10/33/44/550 lbs
E308LFC-O - Stainless Steel	
Wire Diameter	Spool Size
0.030"	2 lbs
0.035"	2 lbs

E71T-11 - Flux Core	
Wire Diameter	Spool Size
0.030"	2/10 lbs
0.035"	2/10 lbs
ER4043 - Aluminum	
Wire Diameter	Spool Size
0.030"	1/10 lbs
0.035"	1/10 lbs

ER308L - Stainless Steel	
Wire Diameter	Spool Size
0.030"	2/10 lbs
0.035"	2/10 lbs
E71T-1C - Mild Steel	
Wire Diameter	Spool Size
0.035"	10/33 lbs
0.045"	10/33 lbs

TIG RODS

ER70S-6 - Mild Steel

Diameter	Package Weight
1/16" x 16"	5 lbs
3/32" x 16"	5 lbs
1/8" x 16"	5 lbs

ER308L - Stainless Steel

Diameter	Package Weight
1/16" x 16"	5 lbs
3/32" x 16"	5 lbs
1/8" x 16"	5 lbs

ER4043 - Aluminum

Diameter	Package Weight
1/16" x 16"	5 lbs
3/32" x 16"	5 lbs
1/8" x 16"	5 lbs

ER70S-2 - Mild Steel

Diameter	Package Weight
1/16" x 16"	6 lbs
3/32" x 16"	6 lbs

WELDING RODS

E6013

Diameter	Package Weight
1/16" x 14"	5 lbs
3/32" x 14"	5 lbs
1/8" x 14"	5 lbs

E6011

Diameter	Package Weight
1/16" x 14"	5 lbs
3/32" x 14"	5 lbs
1/8" x 14"	5 lbs

E7018

Diameter	Package Weight
1/16" x 14"	5 lbs
3/32" x 14"	5 lbs
1/8" x 14"	5 lbs



INE PRODUCTS

FILLER MATERIAL

ER70S-6

Dimension	AWS	Material	Package Weight
0.023"	A5.18	Mild Steel	2/10/33 lbs
0.030"	A5.18	Mild Steel	2/10/33 lbs
0.035"	A5.18	Mild Steel	2/10/33/44 lbs

WELDER SKYLINE 33

Main voltage	1x230V ~ 50-60Hz
Delayed line fuse	16A - 230V ~
Max. absorbed power	4.2 kW
MMA Current range	5 ÷ 140A
TIG Current range	5 ÷ 150A
Efficiency	83%
Idle state	5W
Current regulation	Linear
MMA Duty factor	140A 30%/100A 60%/80A 100%
TIG Duty factor	150A 35%/125A 35%/110A 100%
No-load voltage	67Vdc
Ø MMA Electrodes	1.6 - 2.5 - 3.2 - (4.0)
Protection class	IP23S
Weight	3.6 Kg
Dimension (WxDxH)	111x270x246 mm

Get in touch with us directly

PGN International Group LLC
 14475 NW 60TH Avenue
Miami Lakes - 33014

 (305) 515 - 4052

 sales@pgnwholesale.com

pgnwholesale.com

